

Self-Drilling Screw - For Light Section Composite Panel

Bi-Metal (SO)

Exterior (SO)



HEX



Specifically designed to attach composite panel to light section steel. Self-drilling point with hexagon head.



CORROSION RATING



Urban & industrial areas with a moderate salt atmosphere

CORROSION RATING



Urban & industrial areas with a low salt atmosphere

Product Code	Size (mm)	Socket Size (mm)	FW (mm)	EPDM Washer (mm)	MDT (mm)	Min - Max PT (mm)	ETL (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	-----------	------------------	---------	------------------	----------	-------------------	----------	----------------	--------------------	--------------------

Bi-Metal (Silver Organic)										
BOX										
BMLH70W16	5.5/6.3 x 70	8.0	12.0	16.0	5.0	20 - 50	27	100	16	384
BMLH100W16	5.5/6.3 x 100	8.0	12.0	16.0	5.0	50 - 80	47	100	9	216
TYPE - BMR					SUB TYPE - BMR01					

EXTERIOR (SILVER ORGANIC)										
BOX										
LH82W16B	5.5/6.3 x 82	8.0	12.0	16.0	5.0	32 - 62	41	100	12	288
LH98W16B	5.5/6.3 x 98	8.0	12.0	16.0	5.0	48 - 78	41	100	9	216
LH115W16B	5.5/6.3 x 115	8.0	12.0	16.0	5.0	65 - 95	41	100	8	192
TYPE - RF					SUB TYPE - RF01					
MDT = MAX DRILL THICKNESS ETL = EFFECTIVE THREAD LENGTH FW = FIXED WASHER PT = PANEL THICKNESS										

Fibre Cement Board Screw

Exterior (Silver Organic)



HEX



Self-Drilling - For Light Section Steel



Slash Point - For Timber

Used for securing fibre cement profile sheets to light section steel (max. 5mm). Complete with heavy duty EPDM and stainless steel washer to provide a water-tight seal. Also known as a BAZ washer.

CORROSION RATING



Urban & industrial areas with a low salt atmosphere

Product Code	Size (mm)	Socket Size (mm)	Fixed Washer Ø (mm)	EPDM Washer (mm)	Max. Drill T (mm)	ETL (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	-----------	------------------	---------------------	------------------	-------------------	----------	----------------	--------------------	--------------------

Exterior (Silver Organic)									
BOX									
Self-drilling - for light section steel									
731816	6.3 x 110	8.0	12.0	25.0	5.0	46	50	8	192
731274	6.3 x 130	8.0	12.0	25.0	5.0	46	50	8	192

Slash point - for timber									
731339	6.3 x 130	8.0	12.0	25.0	-	60	50	8	192
TYPE - RF					SUB TYPE - RF06			ETL = EFFECTIVE THREAD LENGTH T = THICKNESS	

Slash Point Screw - For Sheet to Timber

Exterior (SO)

Zinc



HEX



Designed to attach sheet metal (Max 0.9mm) to timber. Slash point for easy pick up.



CORROSION RATING



Urban & industrial areas with a low salt atmosphere

CORROSION RATING



Clean, dry & low humidity environments

Product Code	Size (mm)	Socket Size (mm)	Fixed Washer Ø (mm)	EPDM Washer (mm)	Max. Fixture T (mm)	ETL (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
--------------	-----------	------------------	---------------------	------------------	---------------------	----------	----------------	--------------------	--------------------

Exterior (Silver Organic)									
BOX									
DS25W16B	6.3 x 25	8.0	12.0	16.0	0.9	22	100	35	840
DS32W16B	6.3 x 32	8.0	12.0	16.0	0.9	29	100	15	540
DS45W16B	6.3 x 45	8.0	12.0	16.0	0.9	42	100	15	540
DS45W19B	6.3 x 45	8.0	12.0	19.0	0.9	42	100	18	432
DS60W16B	6.3 x 60	8.0	12.0	16.0	17.0	57	100	18	432
DS60W19B	6.3 x 60	8.0	12.0	19.0	17.0	57	100	12	288
DS80W16B	6.3 x 80	8.0	12.0	16.0	37.0	77	100	12	288
DS100W16B	6.3 x 100	8.0	12.0	16.0	57.0	97	100	9	216
DS125W16B	6.3 x 125	8.0	12.0	16.0	82.0	122	100	8	192
DS150W16B	6.3 x 150	8.0	12.0	16.0	107.0	80 *P/T	100	8	192
TYPE - RF					SUB TYPE - RF01			ETL = EFFECTIVE THREAD LENGTH T = THICKNESS	

TIMBAG									
DS32W16BB	6.3 x 32	8.0	12.0	16.0	0.8	29	120	5	600
DS45W16BB	6.3 x 45	8.0	12.0	16.0	0.8	42	90	5	600
TYPE - BAG					SUB TYPE - BAG11				

Zinc BAG									
ZDS25W16	6.3 x 25	8.0	13.0	16.0	0.8	22	100	20	720
ZDS32W16	6.3 x 32	8.0	13.0	16.0	0.8	29	100	18	648
ZDS45W16	6.3 x 45	8.0	13.0	16.0	0.8	42	100	14	504
ZDS60W16	6.3 x 60	8.0	13.0	16.0	17.0	57	100	12	432
ZDS80W16	6.3 x 80	8.0	13.0	16.0	37.0	77	100	10	360
ZDS100W16	6.3 x 100	8.0	13.0	16.0	57.0	97	100	8	288
TYPE - RF					SUB TYPE - RF02				

*P/T = Partially Threaded