

Drywall Screws




Dense Board Screw

Black Phosphate



CORROSION RATING
1 2 3 4 5
 Clean, dry & low humidity environments



Designed for attaching dense board to timber stud work. The super sharp point and high low thread is specifically designed for an excellent fix into timber.

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX (DRIVER BIT INCLUDED)					
00030DRYD	3.9 x 30	PH2	1,000	16	384
00045DRYD	3.9 x 45	PH2	1,000	8	192
00055DRYD	3.9 x 55	PH2	1,000	6	144
TYPE - DRY			SUB TYPE - DRY03		

Reverse Thread Screw

Black Phosphate



CORROSION RATING
1 2 3 4 5
 Clean, dry & low humidity environments



The reverse thread is designed to assist countersinking in dense board or hard boards.

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX (DRIVER BIT INCLUDED)					
00042DRYR	3.9 x 42	PH2	1,000	9	216
TYPE - DRY			SUB TYPE - DRY04		

Self-Drilling Screw

Zinc




CORROSION RATING
1 2 3 4 5
 Clean, dry & low humidity environments



Self-drilling point to aid fixing plasterboard to wall /ceiling track systems with a max. of 2.0mm thickness. Note: 4.2 diameter screws drill 3.0mm and 4.8 diameter screws drill 4.0mm)

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX (DRIVER BIT INCLUDED)					
00025PSDD	3.5 x 25	PH2	1,000	15	384
00032PSDD	3.5 x 32	PH2	1,000	12	324
00038PSDD	3.5 x 38	PH2	1,000	12	288
00042PSDD	3.5 x 42	PH2	1,000	12	216
00050PSDD	3.5 x 50	PH2	1,000	9	144
00055PSDD	3.5 x 55	PH2	500	6	288
00065PSDD	3.9 x 65	PH2	500	12	288
00075PSDD	4.2 x 75	PH2	500	12	192
00100PSDD	4.8 x 100	PH2	500	8	144
00125PSDD	4.8 x 125	PH2	100	6	540
TYPE - PSD			SUB TYPE - PSD01		
TIMBAG					
00032PSDDB	3.5 x 32	PH2	400	5	600
00042PSDDB	3.5 x 42	PH2	320	5	600
TYPE - BAG			SUB TYPE - BAG10		

Cement Board Screws



Twin-Cut Point

Exterior Plus



CORROSION RATING
 1 2 3 4 **5**
 Clean, dry & low humidity environments



Twin-cut point with a hi-low thread for fixing to timber and thin sheet metal (max. 0.6mm)

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
NEW SIZE					
BOX (DRIVER BIT INCLUDED)					
217789	4.2 x 25	PH2	200	50	1,200
217283	4.2 x 32	PH2	200	50	1,200
217796	4.2 x 42	PH2	200	35	840
TYPE - CBS			SUB TYPE - CBS01		

Self-Drilling Point

Exterior Plus



CORROSION RATING
 1 2 3 4 **5**
 Clean, dry & low humidity environments



Self-drilling point with self-tapping thread for fixing to steel (max. 3.0mm)

Product Code	Size (mm)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX (DRIVER BIT INCLUDED)					
217154	4.2 x 32	PH2	200	50	1,200
217228	4.2 x 42	PH2	200	35	840
TYPE - CBS			SUB TYPE - CBS01		



Metal Framing Screws

Page 46