

Metal Framing Screws



Low Profile - Pan Head

Exterior (Silver Organic)



Urban & industrial areas with a low salt atmosphere



STEEL

A light duty metal to metal screw with a reduced pan to give a flush finish. Silver organic plated to withstand over 500 hours salt spray test.

Product Code	Size (mm)	Max. Drilling Thickness (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX (DRIVER BIT INCLUDED)					
LPP16	4.8 x 16	4.0	500	15	768
TYPE - MFS			SUB TYPE - MFS01		

Low Profile - Wafer Head

Exterior (Silver Organic)



Urban & industrial areas with a low salt atmosphere




STEEL

A light duty metal to metal screw with a large flat surface under the head, making it ideal for fixing thinner sheet material when a flush finish is required. Silver Organic plated to withstand over 500 hours salt spray test.

Product Code	Size (mm)	Max. Drilling Thickness (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX (DRIVER BIT INCLUDED)					
22LPW	4.8 x 22	4.0	200	35	840
TYPE - MFS			SUB TYPE - MFS01		

Low Profile - Pancake Head

Exterior (Silver Organic)



Urban & industrial areas with a low salt atmosphere



STEEL


A medium duty metal to metal screw with a large flat surface under the head, making it ideal for fixing thinner sheet material when a flush finish is required. Silver organic plated to withstand over 500 hours salt spray test.



Product Code	Size (mm)	Max. Drilling Thickness (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX (DRIVER BIT INCLUDED)					
FP19	5.5 x 19	5.0	500	16	540
FP26	5.5 x 26	5.0	500	16	384
TYPE - MFS			SUB TYPE - MFS01		

Pan Head

Zinc



Clean, dry & low humidity environments



STEEL

A light duty metal to metal screw with a phillips recess used for interior applications.

Product Code	Size (imp.)	Max. Drilling Thickness (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
00658PPSD	6 x 3/4	2.5	1,000	15	540
00061PPSD	6 x 1	2.5	1,000	16	384
07716PPSD	7 x 7/16	2.5	1,000	15	540
00812PPSD	8 x 1/2	3.0	1,000	15	540
812PSD	8 x 1/2	3.0	200	15	2,700
00834PPSD	8 x 3/4	3.0	1,000	16	384
834PSD	8 x 3/4	3.0	200	75	2,700
00081PPSD	8 x 1	3.0	1,000	12	288
81PSD	8 x 1	3.0	200	75	2,700
TYPE - PPS			SUB TYPE - PPS01		

Pan Head

Zinc



Clean, dry & low humidity environments



STEEL

A light duty metal to metal screw with a square recess used for interior applications.

Product Code	Size (imp.)	Max. Drilling Thickness (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
00812SPSD	8 x 1/2	3.0	1,000	15	540
TYPE - PPS			SUB TYPE - PPS01		

Wafer Head

Zinc



Clean, dry & low humidity environments

SELF-DRILLING POINT
EN 10666:2008



SHARP POINT



STEEL THIN SHEET

Used when constructing drywall track and ceiling track systems to stitch the track together

Product Code	Size (mm)	Max. Drilling Thickness (mm)	Pack Qty (pcs)	Carton Qty (packs)	Pallet Qty (packs)
BOX					
Self-drilling point					
08916WHSD	4.2 x 13	3.0	1,000	15	360
00016WHSD	4.2 x 16	3.0	1,000	16	288
00019WHSD	4.2 x 19	3.0	1,000	12	288
00025WHSD	4.2 x 25	3.0	1,000	12	144
Sharp point					
08916WHSP	4.2 x 13	0.6	1,000	15	540
TYPE - WHS			SUB TYPE - WHS01		